

407 C Compact rig



407 C Technical Data

ENGINE

Diesel Engine	Cat C-4.4. Tier 4 Final
Power	93,6 kW
Tractive power	13 000 kg
Shoe width	400 mm
Weight std. type from	7 000 kg

FEEDER

Feed length	4 000 kg
Feeder force	3 500 kg
Pull up	7 000 kg
Mast winch	450 kg
Drill table	Ø230 mm
Feed Extention	1 000 mm
Rapid feed	0,60 m/sec
Rapid pull up	0,60 m/sec
Pipe wrench cylinder	Ø 80 mm

ROTATION UNIT


Torque	2 300 / 4 600 Nm
Rotation speed	0-144 / 0-72 rpm
Spindel thread	AP 2 7/8"IF-API2 3/8"REG

OTHER


Pipe rack capacity	96 pcs. 76*3000 mm
Track speed	2,5 / 4,0 km/h
Battery	2 x 50 Ah dry
Hydr. tank	170 L
Diesel Tank	120 L

OPTIONAL EQUIPMENT

Main winch, 4000 kg.
Welding machine
Water pump
Diverter housing



Total height can be reduced to approx. 2400 mm



From the very first Qmatec /Nemek produced rig in 1966, our rigs have been developed and improved in close collaboration with visionary customers. Our employees have long experience and are proud of their profession. Our service people are available where you are, 24-hours a day. This ensures quality throughout the entire process and helps you to be profitable every day – year after year.



407 C
www.qmatec.no
Additional technical data
More pictures

Qmatec Drilling AS

Verkstadvegen 12, 3890 VINJE

Phone: +47 35063400

E-mail: mail@qmatec.com

Web.page: www.qmatec.no